

Technical Data

Eurobind 1300/1300 PUR

Performance

Mechanical	1,300 cycles/h
------------	----------------

Clamps

Number of clamps	4
------------------	---

Block formats

Block width	120 mm – 300 mm (4.72 in – 11.81 in)
-------------	---

Block height	145 mm – 360 mm (5.71 in – 14.17 in)
--------------	---

Block thickness	2 mm – 45 mm (0.08 in – 1.77 in)
-----------------	-------------------------------------

Signature grammage	60 gsm – 170 gsm
--------------------	------------------

Cover formats

Overall cover width	242 mm – 685 mm (9.53 in – 26.97 in)
---------------------	---

Cover height	145 mm – 370 mm (5.7 in – 14.57 in)
--------------	--

Width of front/ back cover	120 mm – 320 mm (4.72 in – 12.60 in)
-------------------------------	---

Cover grammage	120 gsm – 300 gsm
----------------	-------------------

Spine preparation station

Milling depth	0 mm – 3 mm (0 in – 0.12 in)
---------------	------------------------------

Horizontal cover feeder

Max. pile height	150 mm (5.91 in) depending on material
------------------	---

Scoring	Double or quadruple
---------	------------------------

Distance between spine and ornamental scores	6 mm (0.24 in)
---	----------------

Power supply in Europe

400 V, 50 Hz, 3 phases + N + PE/18 A (20 A)/9.9 kVA

Power supply in the U.S.

220 V, 60 Hz, 3 phases + PE/25 A (25 A)/7.6 kVA

Compressed air supply

Working pressure	6 bar
------------------	-------

Compressed air consumption	510 NI/min (free of oil and water)
-------------------------------	---------------------------------------

Dimensions and weight of Eurobind 1300/1300 PUR

Length × width × height	4,085 mm × 2,565 mm × 1,455 mm (13.40 ft × 8.42 ft × 4.77 ft)
-------------------------	--

Weight	Approx. 2,200 kg (4,850 lbs)
--------	------------------------------